

Compact HE rectifier for rail and power utilities applications

Applications in these markets demand state of the art, reliable and safe DC power systems. Flatpack S delivers an industry leading power density in its segment, many safety functions, wide operating temperature range and superb reliability in its small 217mm deep housing.

Used in the 3U rack with Smartpack S controller, the Flatpack S rectifiers cover 2 to 8kW applications using a minimum of space, less than 18 liters, and low heat dissipation.



Flatpack S 24V Rectifier

24/1000 HE

Doc 241122.205.DS3 – v2.1

APPLICATIONS

RAILWAY & METRO

- Control and protection

POWER UTILITIES

- Control and monitoring systems.
- Alarm systems
- PLC systems



3U 8kW system



1U 3kW bulk feed power shelf (PN: 268035)



2pos standalone power shelf (PN: 241122.903)

KEY FEATURES

- SMALL
- SHORT
- POWER DENSE, 26 W / CU IN
- HIGH EFFICIENCY
- ORING PROTECTION ON OUTPUT
- HOT PLUG-ABLE
- VOLTAGE KEYING



Smartpack S controller

Flatpack S 24V Rectifier

Doc 241122.205.DS3 – v2.1

Model	24/1000 HE
Part number	241122.205
INPUT DATA	
Voltage (nominal range)	185 V _{AC/DC} - 305 V _{AC} / 300 V _{DC}
Voltage (operating range)	85 V _{AC/DC} - 305 V _{AC} / 300 V _{DC}
Frequency (nominal / range)	DC, 45 - 66 Hz / 0-66 Hz
Maximum current	5.9 A _{RMS}
Power Factor	> 0.99 at 50% load or more
Protection	Fuse Shutdown above 305 V _{AC} / 300 V _{DC}
OUTPUT DATA	
Voltage (default)	26.7 V _{DC}
Voltage (adjustable range)	21.5 - 28 V _{DC}
Max power, nominal input	1000 W
Max power, @ 85 V _{AC/DC}	440 W
Max current	41.7 A (@V _{OUT} < 24 V _{DC})
Current sharing	±5% of maximum current from 10 to 100% load
Static voltage regulation (10-100% load)	±0.5%
Dynamic voltage regulation	±5.0% for 10-90% or 90-10% load variation, regulation time < 50ms
Hold up time	>20ms; output voltage > 21 V _{DC}
Ripple	< 150 mV _{PP} , 30 MHz bandwidth
Protection	Blocking OR-ing Diode, Short circuit proof, Over voltage protection and High temperature protection
OTHER SPECIFICATIONS	
Peak Efficiency	92.5 %
Isolation	3.0 kV _{AC} – input and output, 1.5 kV _{AC} – input earth, 0.5 kV _{DC} – output earth
Alarms (Red LED)	Low mains shutdown, High and low temperature shutdown, Rectifier Failure, Overvoltage shutdown on output, Fan failure, Low voltage alarm, CAN bus failure
Warnings (Yellow LED)	Rectifier in power de-rate mode, Remote battery current limit activated, Input voltage out of range, flashing at overvoltage
Normal (Green LED)	Input and output ok
Potential alarm relay (normally closed)	Opens on alarms and mains outage
MTBF (Telcordia SR-332 Iss.I method III (a))	> 300 000 (@ T _{ambient} : 25 °C)
Operating temperature (5 - 95% RH non-cond.)	- 40 – 85°C [-40 – 185°F]
Max output power de-rates above temp / to	45°C [+113°F] / 400 W
Storage temperature	-40 to +85°C (-40 to +185°F), humidity 0 - 99% RH non-condensing
Dimensions[WxHxD] / Weight	72 x 41.5 x 217mm (2.83 x 1.63 x 8.54") / < 850 g (1.9 lbs)
DESIGN STANDARDS	
Electrical safety	EN 60950-1:2006+A11:2009+A1:2010+A12:2011, UL 60950-1:2011
EMC	EN 61000-6-1:2007, -6-2:2005, -6-3:2007 + A1:2011, -6-4:2007 + A1:2011, TS 61000-6-5, EN 300 386:v1.6.1, FCC CFR 47 Part 15:2013
Environment	ETSI EN 300 019: 2-1 (Class 1.2), 2-2 (Class 2.3) & 2-3 (Class 3.2) 2011/65/EU (RoHS) & 2008/98/EC (WEEE)

Specifications are subject to change without notice